

Lift chart for standard main boom 12.7 t counterweight

Liebherr HS825D

Capacities in metric tons for boom lengths (11 m - 47 m) - with 160 kN winches														
Radius	Boom length (m)													Radius
	11	14	17	20	23	26	29	32	35	38	41	44	47	
m	t	t	t	t	t	t	t	t	t	t	t	t	t	t
4	43.5	40.6												4
5	32.4	30.7	29.2	27.7	23.3									5
6	25.7	24.6	23.6	22.5	21.6	20.8	19.9							6
7	20.5	20.4	19.7	18.9	18.2	17.6	16.9	16.3	15.7	15.0				7
8	16.9	16.9	16.8	16.2	15.7	15.2	14.6	14.1	13.7	13.2	12.7	12.4		8
9	14.3	14.3	14.3	14.2	13.7	13.3	12.9	12.4	12.0	11.7	11.3	11.0	10.6	9
10	12.3	12.4	12.4	12.3	12.2	11.8	11.5	11.1	10.8	10.4	10.1	9.8	9.4	10
12	9.6	9.6	9.7	9.6	9.6	9.6	9.3	9.0	8.7	8.4	8.2	7.9	7.6	12
14		7.8	7.8	7.7	7.7	7.7	7.6	7.4	7.2	7.0	6.8	6.5	6.3	14
16			6.4	6.4	6.4	6.3	6.3	6.2	6.1	5.9	5.7	5.5	5.2	16
18			5.4	5.4	5.4	5.3	5.3	5.2	5.1	5.0	4.8	4.6	4.4	18
20				4.6	4.6	4.5	4.5	4.4	4.3	4.2	4.1	3.9	3.7	20
22					3.9	3.9	3.8	3.7	3.7	3.6	3.5	3.3	3.1	22
24						3.3	3.3	3.2	3.2	3.1	3.0	2.8	2.7	24
26						2.9	2.8	2.8	2.7	2.6	2.6	2.4	2.3	26
28							2.5	2.4	2.3	2.3	2.2	2.1	1.9	28
30								2.1	2.0	1.9	1.9	1.8	1.7	30
32								1.8	1.7	1.7	1.6	1.5	1.4	32
34									1.5	1.4	1.3	1.2	1.2	34
36										1.2	1.1	1.0		36

Information provided is reproduced with kind permission of Liebherr (GB) Ltd. The data shown is correct at the time of issue and Liebherr retains the right to alter any specification without notice. For CPCS testing activities only and not to be used for operational activities. CPCS and its associate businesses make no representation on behalf of Liebherr (GB) Ltd.